



EMME ANTINCENDIO S.r.l.
www.emme-italia.com

22092-61

9 L. Foam FIRE EXTINGUISHER



CLIP DETAIL



FROST RESISTANCE
(UP TO -30°C)

- CYLINDER
Alloy steel, 3 pieces drawing, with clip, epoxypolyestere powder painting, Red Ral 3000.
- EXTINGUISHING AGENT
Water foam.
- PROPELLANT
Dehumidified air or N₂.
- VALVE
CPF M. 30x1.5, brass body, with anti-corrosion treatment.
- USE
A B F fire rating (solid materials, flammable liquids, cooking oils).

Note: image is for illustrative purpose only, the product purchased can has some differences

9 L. foam fire extinguisher, temperature range from -30°C to +60°C, manufactured in accordance to **UNI EN 3-7**, certified according to the directive for pressure equipment PED 2014/68/EU.

Quality Product certification guaranteed by Bureau Veritas Italia.

Suitable for use on fire involving electrical voltages up to 1'000 V, at a distance of 1 mt.

APPROVED/CERTIFIED FIRE EXTINGUISHER:



FIRE RATING :



21

183

40

© REPRODUCTION IS PROHIBITED


9 L. Foam FIRE EXTINGUISHER

TECHNICAL SPECIFICATIONS


FIRE RATING	21 A 183 B 40 F
EXTINGUISHING AGENT	EW-30 foam (100 % Premix MG6 -30)
PROPELLANT	Dehumidified air or N ₂ ,15 Bar at 20°C
TEMPERATURE RANGE	-30°C / +60°C
NOMINAL CHARGE	9 L.
FULL WEIGHT	~ 14 Kg
DIMENSIONS	Height(base-valve) 630 mm Diameter 170 mm
DISCHARGE TIME	34,5 sec.
VALVE TIGHTENING TORQUE	Minimum 45 Nm, Maximum 68 Nm
CYLINDER PRESSURE TEST	PT 27 bar
CYLINDER VOLUME	10,7 L.
SAFETY VALVE	Set between 20 and 24 bar
CYLINDER MATERIAL	Alloy steel
EXTERNAL/INTERNAL TREATMENT	Sandblast and epoxypolyestere powder painting, Red Ral 3000 colour/ Internal plastic lining

PACKAGING

STANDARD : maximum 40 pieces for pallet
(40 pieces for box, max 1 box for pallet)
Pallet dimensions 100x120x80(h) cm




SINGLE PACKAGING
ON REQUEST:
- maximum 40 pieces
on pallet 100x120



Note: the packaging quantities and measurements are indicative and can be subject at changes

MAINTENANCE AND INSTALLATION

For outdoor or marine installation is recommended to protect the fire extinguisher with cover or box. Maintenance according to the rules in use in utilization country.



SPARE PARTS

NUMBER	DESCRIPTION	CODE
1	Valve M. 30x1.5	0212CS
2	Cylinder	0111-2
3	PVC dip tube	0155-1
4	Label	0087-61
5	Hose with dispensing nozzle	0293
6	Safety pin	0282C
	Safety valve	0261C
	Safety pin seal	0285
	EW-30 foam (9 L. recharge, ready to use)	2055-5
OPTIONAL	Wall-mounted bracket for cylinder with clip, red painting	3036

File name	Code	Date	Rele.	Check	Rev.	Pag.
ds_22092-61	22092-61	07/05/19	M.R	MR	1	2

EMME ANTINCENDIO S.r.l
Via del Molino, 40 - 52010 Corsalone (AR) - Italy
info@emme-italia.com - Tel. +39.0575.511320
Others Emme Antincendio s.r.l. warehouses in Italy : Milano - Padova - Reggio Emilia
P.IVA/ C.F. 11208251006 - R.E.A. FI-632545