Technical Manual





www.emme-italia.com

Via del Molino, 40 - 52010 Corsalone (AR) - Italy - info@emme-italia.com - Tel. +39.0575.511320

Other branches in Italy: Milano - Padova - Roma - Palermo - Cagliari - P.IVA/ C.F. 11208251006 - R.E.A. AR-159122

21021-1: Portable Fire Extinguisher, 2 Kg ABC Powder



- CYLINDER
 In high-strength alloy steel,
 deep drawing, external powder painting Red Ral 3000.
- EXTINGUISHING AGENT ABC Powder - MAP 20 %.
- PROPELLANT
 Dehumidified air or nitrogen (N₂).
- VALVE
 M. 30x1.5, brass body, levers with red painting Ral 3000.
- USE
 A B C fire rating
 (solid materials, flammable liquids, flammable gas).

Note: image is for illustrative purpose only, the product purchased can has some difference

2 Kg powder fire extinguisher, temperature range from -30°C to +60°C, manufactured in accordance to **UNI EN 3-7 (D.M. 7.1.2005)**, approved Marine Equipment Directive **MED 2014/90/EU**, certified according to the directive for pressure equipment PED 2014/68/EU. Manufactured according at productions checks as agreed with **EN 3-10**. Quality Product certification guaranteed by Bureau Veritas Italia.

Suitable for use on fire involving electrical voltages up to 1000 V, at a minimum distance of 1 meter.

APPROVED/CERTIFIED FIRE EXTINGUISHER:











FIRE RATING :







13

89



File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
21021-1_Technical manual	Technical manual	21021-1	09/08/2024	M.R		2	1/3

REPRODUCTION IS PROHIBITED

21021-1: Portable Fire Extinguisher, 2 Kg ABC Powder

INSTALLATION

MAINTENANCE

The installation and the control and/or recovery operations of fire extinguisher must be performed by qualified technician and in accordance to current regulations on the matter

USE

The technician will carry out annual inspection for check the internal pressure and after all other steps planned during the fire extinguisher useful life.

Any tampering or operation performed by unqualified technician, void the product warranty. If possible, is recommended to place fire extinguisher in a dry place, protected from atmospheric agents.

For installation, use and maintenance follow as indicated in file: EPP_1_ENG


TECHNICAL SPECIFICATIONS

FIRE RATING	13 A 89 B C
EXTINGUISHING AGENT	ABC powder - MAP 20 % EPW 18462 (ABC Favorit Tertia - Rühl)
PROPELLANT	Dehumidified air or Nitrogen (N ₂), 15 Bar at 20°C
TEMPERATURE RANGE	-30°C / +60°C
NOMINAL CHARGE	2 Kg
FULL WEIGHT	~ 3,8 Kg (with bracket)
DIMENSIONS	Height (base - valve) 380 +/- 5 mm Diameter (cylinder) 110 +/- 2 mm
DISCHARGE TIME	~ 13,3 seconds
CYLINDER PRESSURE TEST	PT 27 bar
CYLINDER VOLUME	2,5 L
SAFETY DEVICE	Set between 20 and 26 bar
CYLINDER MATERIAL	Alloy steel
TREATMENT	Outside: Sandblast and powder painting, Ral 3000


PACKAGING

(Note: quantities and measurements are indicative and can be subject at changes)

STANDARD
Note: minimum 8 pieces
Maximum nr. 256 pieces for pallet
(32 boxes with 8 pieces for each one)
Pallet dimensions 100x120 cm



ON REQUEST: SINGLE PACKAGING - maximum 192 pieces on pallet 100x120




TRANSPORT DISPOSAL

Land transport: Exemption for the purposes of ADR disposal 594 Ship Transport: IMDG Code – UN 1044 class 2.2 Fire Extinguishers

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
21021-1_Technical manual	Technical manual	21021-1	09/08/2024	M.R		2	2/3

21021-1: Portable Fire Extinguisher, 2 Kg ABC Powder

COMPONENTS AND SPARE PARTS LIST



NUM.	DESCRIPTION	CODE		
1	Valve M. 30x1.5	0211		
1.1	O-ring valve	0201-13		
1.2	Valve stem	0241R		
1.3	Internal spring of the valve	n.a.		
1.4	Test valve for pressure gauge	1163		
1.5	Dip tube holder	n.a.		
1.6	Safety device	0261R		
1.7	Dispensing nozzle	0287		

DE
2-1
85
52
02
71–1
27
2-2
/

The spare part at number 1 includes already all others components indicated from 1.1 to 1.7

"n.a." mean that the component is not available as single spare part

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
21021-1_Technical manual	Technical manual	21021-1	09/08/2024	M.R		2	3/3